



Sweetwater Metal Products model CT2710C-LT-SL LDCPE pipe dispensing trailer meets or exceeds all the safety and quality requirements demanded by today's utility company and pipe installation contractor. The CT2710C incorporates many features to improve the handling, transporting, and dispensing of coiled pipe, which equates to substantial cost savings.

Features:

- **McElroy line Tamer to straighten and re-round the pipe - First designed and fabricated in our shops.**
- **Coil is suspended from ID - Always stays vertical and indexed with tamer.**
- **Powered adjustable Mast - Accepts different coil size's and allows pipe room to align.**
- **Threading Rollers - Guides pipe into tamer and supports the pipe.**
- **Self Loading - Self storing load arm. Built in powered hoist.**



281-556-1661 • secoronline.com • info@secoronline.com

- Loads vertical or horizontal coils.
- Outriggers - Stabilize the trailer while loading coil.
- Side Loading - Nothing to remove, just open the gate and hoist the coil in.
- Totally Self Contained - Nothing else required. No reel required.
- Safety Cage - Protects workers from inadvertent release of coiled energy.
- Adjustable Side Gate - Adjusts to the width of the coil.
- Hydraulic Power Unit - Gas driven.
- Meets DOT regs. - Transport the trailer with coil loaded if required.
- Requires only two workers to operate.
- Structural Steel Tubing.

Specifications		(CT2710C-LT-SL)
Overall width		8 Foot
Traveling Height		10 Foot
Overall Length		27 Foot
GVWR		9,850 Lbs.
Capacity		3,200 Lbs.
Empty Weight		6,300 Lbs
Coupler		Pintle Eye
Tires		ST225/75R15 LRD
Protected Lights		
Electric Brakes		
Coil Sizes		CT2710C-LT-SL
Maximum Outside Diameter		125 Inches
Minimum Inside Diameter		48 Inches
Maximum Width		66 Inches