



DBS-10A

Service Size Squeeze Tool

1" IPS Integrated Single Bar

The smallest tool in Mustang's lineup, the DBS-10A employs an open frame design, which permits easy application on service PE pipe. Gap stops are welded to the upper jaw and grease fittings are provided for power screw and thrust bearing lubrication.

Static electric grounding is accomplished using a SEG-30 Grounding Rod attached to the upper jaw.

Weight: 6lbs
 Dimensions: 8.75" Height
 Capacity: Specify (1) Size (see table)

Gap stops are welded to the upper jaw on DBS-10A Service Tools. A gap stop can protect more than one pipe size if a similar wall thickness exists. (Example: 1/2" CTS SDR-7 and 1" CTS SDR-11.5 can be squeezed using a common .155 size gap stop. Custom gap stops are available upon request.)

Pipe Size	Nominal Wall Thickness	SDR	Gap Stop	%Max Squeeze
IPS 1/2"	.090	9.3	.155	18
CTS 1/2"	.090	7	.147	22
	.104	6	.172	21
IPS 3/4"	.095	11	.155	25
CTS 3/4"	.077	11	.125	24
	.090	9.7	.155	18
IPS 1"	.119	11	.210	22
CTS 1"	.090-.101	11-12.5	.155	29
CTS 1-1/4"	.090	15	.155	21
	.121	11	.210	19