



ECCENTRIC REDUCER

SCALE: NTS

DIMENSIONS					
SIZE IPS	A	B	C	D	E
* 12x8	12.75	8.625	14.00	7.00	7.00
12x10	12.75	10.75	14.00	7.00	7.00
14x12	14.00	12.75	14.00	7.00	7.00
* 16x12	16.00	12.75	14.00	7.00	7.00
16x14	16.00	14.00	14.00	7.00	7.00
18x16	18.00	16.00	14.00	7.00	7.00
* 20x16	20.00	16.00	14.00	7.00	7.00
20x18	20.00	18.00	14.00	7.00	7.00
22x20	22.00	20.00	14.00	7.00	7.00
* 24x20	24.00	20.00	18.00	9.00	9.00
24x22	24.00	22.00	18.00	9.00	9.00
26x24	26.00	24.00	18.00	9.00	9.00
28x26	28.00	26.00	18.00	9.00	9.00
30x28	30.00	28.00	18.00	9.00	9.00

NOTES

1. ALL DIMENSIONS ARE IN INCHES.
2. FITTINGS ARE MANUFACTURED FROM PE4710, MEETING ASTM D3350 CELL CLASSIFICATION 445574C FOR BLACK OR 445574E FOR COLOR STRIPES.
3. FITTINGS MEET ASTM F2206: STANDARD SPECIFICATION OF IPS FABRICATED FITTINGS OF BUTT-FUSED POLYETHYLENE.
4. FITTINGS MEET ASTM D3261 FOR BUTT HEAT FUSION OF POLYETHYLENE PLASTIC FITTINGS FOR POLYETHYLENE PLASTIC PIPE AND TUBING.
5. FITTINGS ARE FABRICATED IN ACCORDANCE TO ASTM F2620 STANDARD FUSION PROCEDURES.
6. WPR BASED ON RESIN PE4710 FOR WATER AT 73° F.
7. DIMENSIONAL TOLERANCES: +/- 2".
8. ANGLE TOLERANCES: +/- 2.0°.
9. CONTACT SECOR FOR SIZES NOT SHOWN.
10. * = SDR11 AND SDR17 ONLY.

A	ISSUED FOR CLIENT REVIEW	-	CMG
REV	DESCRIPTION	DATE	NAME

SECOR

17321 GROESCHKE ROAD HOUSTON, TX. 77084
PH.# 281-556-1661 FAX# 281-556-1683

CONFIDENTIAL NOTICE / CONTROLLED DOCUMENT
Dissemination of this information contained herein is prohibited

TITLE:				
SECOR IPS FABRICATED FITTING ECCENTRIC REDUCER				
DATE	DRAWN BY	CHECKED BY	DRAWING NO.	REV
10/15/20	CMG	-	-	A

SDR	WPR
7	336
9	252
11	200
17	126