

## GLS-26

## **Ground Level Squeeze Tool**

The GLS-26 is an upgrade to our field proven GLS-20 Emergency Tool by providing direct dial squeeze control. The new color coded gap stops, along with an emergency setting, enables you to safely squeeze off every PE pipe size from 1/2" CTS through 2" IPS — with all settings and pipe sizes cross-referenced on a frame-mounted color chart. Simply dial in the prescribed gap stop by rotating the stainless steel, color coded disc. A dual set of spring-action "whiskers" quide you in centering the jaws squarely on the pipe. Turning the tool's 12" handle generates up to 10,000lbs of squeeze force, while its upper-frame torque handle provides added leverage. Light and durable, the trim GLS-26 is designed with the same unparalleled 3:1 strength factor bred into the entire Mustang family. For further safety, we've attached a solid copper grounding device, with 5' strap and 3/8"x12" spike, as standard equipment.



Weight: 19lbs
Dimensions: 59"x 6.5"
Capacity: See Table Below

Emergency Gap .000 Any Size 1/2"CTS – 2"IPS 1/2"IPS, DR-9.3 1/2"CTS, DR-7 1"CTS, DR-12.5 3/4"CTS, DR-9.7 .090-.095 Wall 3/4"IPS, DR-11 1"CTS, DR-11/11.5 1-1/4"CTS, DR-15 .095-.101 Wall 1"IPS, DR-11 1"CTS, DR-9 .119-.121 Wall

1-1/4"IPS, DR-10/11 1-1/2"IPS, DR-11 .151-.173 Wall 2"IPS, DR-11 .216 Wall

