

Basic Specifications

Steel Pipe Squeezer – 5230T

- Closes 3" 4" Steel Pipe, Sch 40 & Sch 80
- Capacity 75 Tons
- Dimensions: 13 1/2" x 32 1/2"
- Shipping Weight: 265 Lbs
- Single Hydraulic Ram to ensure even pressure while squeezing the steel pipe closed.

• Mechanical Lock Nut – Used when steel pipe closure has been accomplished. Lock Nut is screwed down against the cylinder, at which time hydraulic pressure can be relieved, leaving the Pipe Squeezer secure on the mechanical lock nut, NOT on hydraulic pressure.

• Lower Jaw Release Pin – For quick & easy opening of Lower Jaw to remove Pipe Squeezer from the Steel Pipe.

- Upper Jaw & Ram assembly are self-retracted
- Quick Release fittings are used to connect & disconnect Pump Hose from Pipe Squeezer.

• Lifting Handle welded to the Cylinder Support for ease of handling.

Air Operated Hydraulic Pumping Unit *Model 5336-A20*

- Air Driven Pumping Unit with Hydraulic Reservoir
- 20 Foot Long Hydraulic Hose
- Hydraulic Hose with Quick Disconnects
- Pressure Gauge Assembly
- Maximum Operating Pressure 10000 psig

PRODUCT DATA SHEET 3" to 4" STEEL PIPE SQUEEZER

Model 5230T, 75 Ton Capacity





TIME TESTED, FIELD PROVEN!

5336-A20 Air Pump



REGENT TOOLS has continued its research & development program aimed at providing the Finest Tools & Accessory items to meet the high standards of today's industry.

Regent

Tools, Inc.

Regent Tools, Inc. 17321 Groeschke Road Houston, TX 77084 USA Ph: 281-556-1661Fax: 281-556-1683www.regentools.com