



# MODEL: CT2710C-LT-SL

## SPECIFICATIONS

### DESCRIPTION

MODEL – CT2710C-LT-SL  
GVWR – 9,850 lbs.  
Empty Weight – 6,300 lbs.  
Carrying Capacity – 3,200 lbs.  
Overall Length – 27 ft.  
Overall Width – 96 in.  
Overall Height – 8 ft. – 4 in.  
Maximum Coil OD – 125 in.  
Minimum Coil ID – 48 in.  
Maximum Width – 66 in.

### RUNNING GEAR

Dual Axle – 5,200 lbs. Each  
Brakes – Electric  
Tires – ST225/75R15 LRD  
Wheels – 15 x 6 6 Bolt Mod  
Suspension – Slipper Leaf Spring

### FRAME

Main Frame – Double Frame – 8 x 2 x 3/16" Tube  
6 x 4 x 3/16" Tube  
Coil Cage – 2 x 2 x 1/4" Square Tube  
Mast Uprights Inside – 6 x 2 x 3/8" Rect. Double Tube  
Mast Uprights Outer – 7 x 5 x 3/16" Rect. Tube  
Mast Rollers – 5" Sch. 40 Pipe  
Threading Rollers – 3 1/2" Sch 40 Pipe  
Interior Roller – 3 1/2" Sch 40 Pipe  
Tongue – 6 x 4 x 3/16" Tube with Pintle Eye  
Fenders – 12 ga.

### ELECTRICAL

Plug – 7 RV Molded Plug  
Wiring – Enclosed in Tube with Junction Box  
Lights – Standard LED

### SAFETY

Chains – 3/8" with Heavy Duty Hook & Safety Latch  
Breakaway – Battery, Battery Box and Switch  
Decals – Warning Decals and Reflective Tape

### INCLUDED ACCESSORIES

McElroy 4-6 in. LineTamer® (LT0048)

### FINISH

Sherwin-Williams Paint  
Industrial Urethane Yellow

### HYDRAULICS

Motor – 5.5 HP Honda Motor  
Hydraulic Winch  
Valve – One 1 Spool Valve and One 3 Spool Valve  
Hydraulic Arm Cylinder – 5 x 24 in. Tie Rod  
Interior Roller Cylinder – 2 x 12 in. Tie Rod  
Threading Roller Cylinder – 2 1/2 x 6 in. Tie Rod

### AVAILABLE OPTIONS

Optional McElroy 2" LineTamer® (LT0122)  
Optional 2" LineTamer® Mount (LTM2)  
Optional 3" Re-Round Kit (LT0037)  
Optional Hydraulic Operated Mast (HM1)

