



CONCENTRIC REDUCER

SCALE: NTS

DIMENSIONS

SIZE IPS	A	B	C	D	E
* 12x8	12.75	8.625	14.00	7.00	7.00
12x10	12.75	10.75	14.00	7.00	7.00
14x12	14.00	12.75	14.00	7.00	7.00
* 16x12	16.00	12.75	14.00	7.00	7.00
16x14	16.00	14.00	14.00	7.00	7.00
18x16	18.00	16.00	14.00	7.00	7.00
* 20x16	20.00	16.00	14.00	7.00	7.00
20x18	20.00	18.00	14.00	7.00	7.00
22x20	22.00	20.00	14.00	7.00	7.00
* 24x20	24.00	20.00	18.00	9.00	9.00
24x22	24.00	22.00	18.00	9.00	9.00

NOTES

- ALL DIMENSIONS ARE IN INCHES.
- FITTINGS APPROVED FOR:
 - FM 1613, FM CL250
 - AWWA C906
 - NSF-61
- FITTINGS ARE MANUFACTURED FROM PE4710, MEETING ASTM D3350 CELL CLASSIFICATION 445574C FOR BLACK OR 445574E FOR COLOR STRIPES.
- FITTINGS MEET ASTM F2206: STANDARD SPECIFICATION OF FM CL250S OF BUTT-FUSED POLYETHYLENE.
- FITTINGS MEET ASTM D3261 FOR BUTT HEAT FUSION OF POLYETHYLENE PLASTIC FITTINGS FOR POLYETHYLENE PLASTIC PIPE AND TUBING.
- FITTINGS ARE FABRICATED IN ACCORDANCE TO ASTM F2620 STANDARD FUSION PROCEDURES.
- FITTINGS .
- WPR BASED ON RESIN PE4710 FOR WATER AT 73° F.
- DIMENSIONAL TOLERANCES: +/- 2".
- ANGLE TOLERANCES: +/- 2.0°.

A	ISSUED FOR CLIENT REVIEW	-	CMG
REV	DESCRIPTION	DATE	NAME

SECOR

17321 GROESCHKE ROAD HOUSTON, TX. 77084
PH.# 281-556-1661 FAX# 281-556-1683

CONFIDENTIAL NOTICE / CONTROLLED DOCUMENT
Dissemination of this information contained herein is prohibited

TITLE: SECOR
FM CL250
CONCENTRIC REDUCER

DATE	DRAWN BY	CHECKED BY	DRAWING NO.	REV
10/15/20	CMG	-	-	A